

Series ASR Audible and Audible Strobe



Description:

The Series ASR Audible and Audible Strobe products provide a range of warning alarms and strobes designed to cope with harsh environments providing weatherproof protection. Design features are incorporated to ensure safer and easier installation, while providing flexibility with fewer product variants.

Current:	ASR-DC	450MA/MAX
	ASR-AC	115VAC - 130 MA 230VAC - 65 MA
	ASRS-DC	Max 700 MA
Nominal Voltage:	18 - 30VDC, 115/230VAC	
Current Consumption (tone dependant):	Between	
Sound Output (tone dependant):	Between 105 - 102dB	
Alarm Tones:	42	
IP Rating:	IP66	
Lens Colour:	Red / Amber / Blue	
Flash Rate:	1 Hz (60 per min)	
Color:	Off White	
Strobe Type:	U-Tube	
Operating Temperature:	-25°C to 70°C	
Monitoring Mode:	Polarizing Diode (DC models only)	
Volume Control:	0 to -10dB	

Features:

- up to 120dB(A) Output
- Three stage alarm (2 programmable - 1 standard)
- More light where required with asymmetric lens
- Easy access for installation with shallow base format
- 42 Tones
- Weatherproof - Indoor/Outdoor

Specification and Ordering Information:

Model Number	Order Code	Description
ASR-DC	4072	Audible only, 24VDC
ASR-AC	4073	Audible only, 115/230VAC
ASRS-A-DC	4074	Audible Strobe, 24VDC, Amber lens
ASRS-R-DC	4075	Audible Strobe, 24VDC, Red lens
ASRS-B-DC	4076	Audible Strobe, 24VDC, Blue lens



WE ENCOURAGE AND SUPPORT NICET CERTIFICATION
3 YEAR WARRANTY
ASR 02/08



NJ Location
273 Branchport Ave.
Long Branch, NJ 07740
P: 800-631-2148
F: 732-222-8707
www.coopernotification.com

FL Location
7565 Commerce Ct.
Sarasota, FL 34243
P: 941-487-2300
F: 941-487-2389

VA Location
P: 877-459-7726
F: 703-294-6560