

Series MID Audible and Audible Strobe



Description:

The Series MID Audible and Audible Strobe is a versatile and rugged alarm designed for industrial environments or areas where there is a requirement for a physically robust and well-protected unit.

Nominal Voltage: 9 to 60VDC, 115/230VAC

Current Consumption (tone dependant): see table below

Sound Output (tone dependant): 105 - 110dB(A)

Alarm Tones: 32

IP Rating: IP66

Color: Off White

Flash Rate: 1 Hz (60/min)

Strobe Type: Xenon

Current Consumption:

MID-AC 27mA @ 115VAC, 14mA @ 230VAC

MID-DC Max. 41mA

MIDS-AC 87mA @ 115VAC, 45mA @ 230VAC

MIDS-DC Max. 90mA @ 24VDC

Operating Temperature: -25°C to 70°C

Volume Control: 0 to -10dB

Features:

110dB(A) Output

Weatherproof

Simple First & Second Installation

Fully Integrated High Efficiency Strobe

32 Alarm Tones

Two Stage Alarm (1 programmable, 1 standard)

Indoor/Outdoor

Specification and Ordering Information:

Model Number	Order Code	Description
MID-DC	4079	Audible only, 9 – 60VDC
MID-AC	4080	Audible only, 115/230VAC
MIDS-A-DC	4081	Audible strobe, 9 – 60VDC, Amber lens
MIDS-A-AC	4082	Audible strobe, 115/230VAC, Amber lens
MIDS-R-DC	4082	Audible strobe, 9 – 60VDC, Red lens
MIDS-R-AC	5230	Audible strobe, 115/230VAC, Red lens
MIDS-B-DC	4083	Audible strobe, 9 – 60VDC, Blue lens
MIDS-B-AC	5232	Audible strobe, 115/230VAC, Blue lens



WE ENCOURAGE AND SUPPORT NICET CERTIFICATION
3 YEAR WARRANTY
MID 02/08



NJ Location
273 Branchport Ave.
Long Branch, NJ 07740
P: 800-631-2148
F: 732-222-8707
www.coopernotification.com

FL Location
7565 Commerce Ct.
Sarasota, FL 34243
P: 941-487-2300
F: 941-487-2389

VA Location
P: 877-459-7726
F: 703-294-6560