

Series SLS Strobe



Description:

The Series SLS Strobe has a wide operating voltage range and automatic synchronization which makes it a universal solution for all types of applications. The Series SLS can be mounted outdoors when used with a DB backbox.

Voltage:	10-60 VDC
Current:	Max. 220mA at 24VDC (includes current surge suppression)
Light Source:	Xenon
IP Rating:	IP65 w/ deep base, IP54 w/ shallow base
Color:	Off White
Flash Rate:	1 Hz (60/min)
Anti-tamper (where fitted):	Normally closed contacts. Contacts open when strobe removed from base
Operating Temperature:	-25°C to 70°C

Features:

- Wide operating voltage up to 60VDC
- Current surge suppression
- Automatic synchronization
- High efficiency
- Constant base performance over voltage range
- Strobe can be locked onto base
- Indoor (Outdoor only with deep base)

Specification and Ordering Information:

Model Number	Order Code	Description
SLS-A-DC	4087	Amber Lens
SLS-R-DC	4088	Red Lens
SLS-B-DC	4089	Blue Lens



WE ENCOURAGE AND SUPPORT NICET CERTIFICATION
3 YEAR WARRANTY
SLS 02/08



NJ Location
273 Branchport Ave.
Long Branch, NJ 07740
P: 800-631-2148
F: 732-222-8707
www.coopernotification.com

FL Location
7565 Commerce Ct.
Sarasota, FL 34243
P: 941-487-2300
F: 941-487-2389

VA Location
P: 877-459-7726
F: 703-294-6560